


# CYLINDER SLEEVE RESLEEVE

CUSTOMER: \_\_\_\_\_  
 SIGNATURE: \_\_\_\_\_  
 PRINT NAME: \_\_\_\_\_  
 DATE: \_\_\_\_\_



8. ALL UNDERCUTS TO BE .125 WIDE  
 .013±.001 DEEP FROM BODY OUTSIDE  
 DIA WITH .015 FILLET RADIUS.

- 7. BREAK ALL EDGES .005/.020
- 6. OD TO BE ROUND WITHIN .001 T.I.R.
- 5. TAPER OF BORE NOT TO EXCEED .001/6"
- 4. TAPER OF OD NOT TO EXCEED .001/6"
- 3. ALL DIA'S TO BE CONCENTRIC WITHIN .001 T.I.R.

2. SURFACES INDICATED TO BE PARALLEL TO EACH OTHER WITHIN .001 AND PERPENDICULAR WITHIN ±1'

1. FINISH 32 OR BETTER

NOTES: UNLESS OTHERWISE SPECIFIED

10. MAT'L: CENTRIFUGALLY CAST DUCTILE IRON  
 SPECIFICATION: ASTM #A-536-84  
 CLASS: 100-70-03  
 TENSILE STRENGTH: 100,000 PSI  
 YIELD STRENGTH: 70,000 PSI  
 % ELONGATION IN 2": 3% MIN  
 HEAT TREATMENT: NORMALIZED PEARLITIC  
 BRINELL HARDNESS NUMBER: 240-290 10mm BALL - 300KG LOAD  
 9. CASTINGS TO BE FREE OF AIR HOLES, COLD FLOW IMPERFECTIONS, AND SURFACE CRACKS

THE INFORMATION DEPICTED HEREIN IS PROPRIETARY DESIGN INFORMATION WHICH IS COPYRIGHTED BY DARTON INTERNATIONAL, INC. NO DUPLICATION OR USE OF THIS INFORMATION IS PERMITTED WITHOUT EXPRESS WRITTEN CONSENT OF DARTON INTERNATIONAL, INC.

DR. BY: CAD DEPT	Dartons International, Inc. Carlsbad, CA USA (800) 713-2786 (760) 603-9895 FAX (760) 603-9629 WWW.DARTON-INTERNATIONAL.COM
DATE: 3/14/2002	
CHK'D BY:	TITLE: CYLINDER SLEEVE - RESLEEVE (A TOL)
MATERIAL:	SIZE: A
HARDNESS:	SCALE: NONE
FILE NO: F:\ACAD_DAT\ Darton\STANDARDS\ORDER FORMS\A RESLEEVE	SHEET 1 OF 1

To complete this form please do the following:

1. Complete the value fields to the left. Move from field to field by pressing the "tab" key.
2. Fill in your contact information below.
3. Print completed form.
3. Sign, date and fax to Darton at (760) 603-9629

NAME:

COMPANY:

PHONE:

FAX:

E-MAIL: